

FIRESTOP Embossed Tape

PRODUCT DESCRIPTION

FIRESTOP Embossed Tape is a high-performance, multilayered, fire-rated tape made from polyester and aluminium foil paired with a cold-weather adhesive. It is engineered for durability, UV exposure, extreme environmental conditions, and fungi resistance.

APPLICATIONS:

- ✓ As a joint tape for the FIRESTOP Duct Wrap-38/25 systems
- As a vapour barrier
- For insulation applications.



- Fire Performance: Tested to AS1530.4 for fire-rated ductwork systems with FRR up to -/120/120, meeting all relevant fire resistance requirements.
- Exceptional Adhesion: Performs reliably in cold and hot, humid environments.
- Cold-Weather Bonding: Maintains a secure seal at temperatures as low as -23°C.
- Zero Permeability: Acts as an effective vapour barrier for insulation cladding and jacketing.
- Durable Design: Highly resistant to punctures and tears, ensuring long-lasting application.
- Versatile and Flexible: Strong yet easy to handle for various applications.
- Convenient Installation: Simple to cut and apply on-site, with no special tools required.



TECHNICAL PARAMETERS

| Property | Typical Value |
|-------------------------------------|-------------------------|
| Material Thickness without liner | 0.14mm (5.5mils) |
| Overlap Adhesion | 66.97 grams/mm |
| Tensile Strength | 7.49 kgf/mm² |
| Bursting Strength | 0.089 kgf/mm² |
| Puncture Resistance | 8.1 kgf |
| Tear Strength | 2.5 kgf |
| Elongation | 59% |
| Water Vapor Permeance | 0.00 perm |
| Service Temperature | from -40°C to 120°C |
| Flame/Smoke Rating | <25/50, Class 1/Class A |
| Width | 100mm & 600mm |
| Colour | Silver |

